

Customized Reports with ODS: DECISION TREE PROCESS FOR USING STYLE DEFINITIONS

#	PROCESS OF CUSTOMIZING STYLE DEFINITIONS
At the <u>[1]</u> level,	Define the <u>level of customization required</u> . This defines the scope of the customization such as overall output font and colors.
To customize <u>[2]</u> ,	Within the level of customization, define <u>what to customize</u> . This defines the actual item to customize such as list of fonts and color names.
Using the <u>[3]</u> style element	Based on the response from [1] and [2], <u>use the appropriate style element</u> . This defines which style elements to use such as fonts and color list.
With the <u>[4]</u> statement.	Within each style element, <u>use the appropriate style attribute</u> for the selected customized item. This defines the code within each style element.

At the <u>[1]</u> level,	To customize <u>[2]</u> ,	Use the <u>[3]</u> style element	With the <u>[4]</u> style attribute
OVERALL OUTPUT FONTS	List of Fonts available	FONTS ❶	/ 'FONT_NAME'=("FONT FACE 1, FONT FACE 2", FONT_SIZE, FONT_WEIGHT, FONT_STYLE, FONT_WIDTH) [Valid options for each FONT style element]
OVERALL COLORS	List of Color Names Parts of the output file with colors from color_list	COLOR_LIST COLORS	/ 'fgA'=cx002288 Assignment of color / 'docfg' = color_list('fgA')
OVERALL DOCUMENT	Body File attributes - background image - output margin	BODY from DOCUMENT ❷	/ BACKGROUNDIMAGE='my_bkgr.bmp' RIGHTMARGIN= 5 LEFTMARGIN= 30
OVERALL TITLES	Text of System Titles - style	SYSTEMTITLE from TITLESANDFOOTERS ❸	Valid options to override default settings.
OVERALL TABLE	Table Style - attributes Footer	TABLE ❹ FOOTER ❺	Valid options to override default settings.
TABLE ROWHEADER STYLE	Table Row Header - style Header	ROWHEADER from HEADER ❻ HEADER ❼	Valid options to override default settings.
HTML	Parts of the HTML file - common text	HTML	Valid options to override default settings.
CONTENTS TITLE FOR HTML DESTINATION	HTML Contents Title - style	CONTENTTITLE from INDEXTITLE ❽	/ PRETEXT = 'Web Site Contents';
MOST STYLE ELEMENTS	Style attributes a. using font definitions and color b. using existing fonts and color	Original Style Element Or Create new Style Element	/ FONT_FACE= FONT_SIZE= FONT_WEIGHT= FONT_STYLE= FONT_WIDTH= BACKGROUND= [Valid options for each Font & Color style element] / BACKGROUND=WHITE FONT=FONTS('EMPHASISFONT') [EMPHASISFONT font is defined in the FONTS Style Element]

